

基本多回转电动执行机构选型资料

选型参数		型号示例: UK11-CD/B3											
关断力矩(Nm)	输出转速(rpm)	U	A/K	X	X	-	C/D/E	D/E		/ X	保护套管		-XX
		类型 A:调节型 K:开关型		1	2	3	4	5	6	速度	D/E	输出轴 B1:大空心轴 B3:小空心轴 A: A型轴 C: 爪型输出轴 D: 轴伸	标准长度 260mm
10 ~ 30	5 ~ 40			1/0	0: F07 1: F10 3: F14 4: F16	连接符	C	D/E	D: 220VAC E: 380VAC	B1:大空心轴 B3:小空心轴 A: A型轴 C: 爪型输出轴 D: 轴伸	标准长度 260mm	0:无 1:标准长度 2:指定长度	其它 - Ex:防爆型
	10 ~ 80						D	D/E					
	20 ~ 160						E	D/E					
20 ~ 60	5 ~ 40			1/0	注: 斜线上方为标配, 下方为选项配置	连接符	C	D/E					
	10 ~ 80						D	D/E					
	20 ~ 160						E	D/E					
40 ~ 125	5 ~ 40			1/4			C	E					
	10 ~ 80						D	E					
	20 ~ 160						E	E					
80 ~ 250	5 ~ 40			3			C	E					
	10 ~ 80						D	E					
	20 ~ 160						E	E					
160 ~ 500	5 ~ 40			4			C	E					
	10 ~ 80						D	E					
	20 ~ 160						E	E					
320 ~ 1000	5 ~ 40			5			C	E					
	10 ~ 80						D	E					
	20 ~ 160						E	E					
320 ~ 1000	5 ~ 40			6			C	E					
	10 ~ 80						D	E					