

底座曲柄式电动执行机构选型资料

选型参数				型号示例: UA11-CD/B3 + F35									
关断力矩(Nm)	全行程时间(秒)	曲柄长度(mm)	U	A/K	XX	-	C/E	D/E	/B3	-XX	+	FXX	
150 ~ 350	20 ~ 160	150/200		A:调节型 K:开关型	11		速度	D/E	D: 220VAC E: 380VAC		其它 -Ex:防爆型	连接符	F35
	10 ~ 80				D/E			F50					
150 ~ 500	20 ~ 160	150/200/250			11		C						F100
	10 ~ 80				D/E		F250V						
320 ~ 1000	20 ~ 160				21		C						F250V
	10 ~ 80				D/E		F400V						
670 ~ 2200	20 ~ 160				11		E						F600V
	20 ~ 160				D/E		F600V1						
1300 ~ 2600	20 ~ 160				21		E						F1000
	10 ~ 80				E		F1000 (4)						
700 ~ 2300	10 ~ 80				31		D						F1000 (8)
	20 ~ 160				E		F2000						
1300 ~ 4500	20 ~ 160				21		E						F2000 (4)
	20 ~ 160				D/E		F2000 (8)						
2800 ~ 6000	20 ~ 160	300/400			31		E						F2000 (16)
	10 ~ 80				E		F4000 (4)						
3000 ~ 10000	10 ~ 80				53		E						F4000 (8)
	20 ~ 160				E		F4000 (16)						
6000 ~ 20000	40 ~ 320	500/650			31		E						F4000 (8)
	80 ~ 640				D/E		F4000 (16)						
12000 ~ 40000	20 ~ 160	600/800			53		E						F4000 (4)
	40 ~ 320				E		F4000 (8)						
	80 ~ 640				33		E						F4000 (16)