

直连式电动执行机构选型资料

选型参数		型号示例: UA11-CD/B3 + S35-F10-0												
关断力矩(Nm)	全程时间(秒)	U	A/K	XX	-	C/E	D/E		/B3	-XX	+	SXX	- FXX	-0/1/2/3/4
			类型			速度	供电电源			其它		减速箱	法兰	输出轴开孔
150 ~ 350	20 ~ 160		A:调节型	11		C	D/E	D: 220VAC	多回转与减速箱连接轴类型	-Ex:防爆型	连接符	S35	F10/F07	0:未开孔 1:带键槽的孔轴 (符合DIN 6885 Part 1)
	10 ~ 80		K:开关型	11		D	D/E	E: 380VAC						
150 ~ 500	20 ~ 160			11		C	D/E							
	10 ~ 80			11		D	D/E							
320 ~ 1000	20 ~ 160			21		C	D/E							
	10 ~ 80			21		D	D/E							
670 ~ 2200	20 ~ 160			11		E	D/E							
	10 ~ 80			21		E	D/E							
1300 ~ 2600	20 ~ 160			31		D	E							
	10 ~ 80			21		E	D/E							
700 ~ 2300	20 ~ 160			31		E	E							
	10 ~ 80			31		E	E							
1300 ~ 4500	20 ~ 160			53		E	E							
	10 ~ 80			31		E	D/E							
2800 ~ 6000	20 ~ 160			21		E	E							
	10 ~ 80			21		E	E							
3000 ~ 10000	20 ~ 160			31		E	E							
	10 ~ 80			31		E	E							
6000 ~ 20000	20 ~ 160			53		E	E							
	10 ~ 80			64		D	E							
12000 ~ 40000	20 ~ 160			43		E	E							
	10 ~ 80			31		E	E							
	40 ~ 320			21		E	D/E							
	80 ~ 640			53		E	E							
	20 ~ 160			43		E	E							
	40 ~ 320			33		E	E							
	20 ~ 160					E	E							
	80 ~ 640					E	E							